

**SPECIFICATIONS – Bramble Meadows, Exeter, NH**

Date: 04/29/2020

Revised date:

BUYER: General Specs

SELLER/CONTRACTOR: Chinburg Builders, Inc. (CBI)  
3 Penstock Way, Newmarket, NH 03857

603-868-5995  
603-389-9011 fax

JOB LOCATION: Exeter, NH

-----  
**SCOPE**

These specifications are intended to include all labor, materials, and services necessary for construction. All articles or materials are specified in such a manner that an equal material or product of the same quality can be substituted at the discretion of CBI. Changes to these specifications may be negotiated. Work not specifically described below or shown in attached drawings will not be considered unless required by applicable codes, when the minimum acceptable will be assumed.

-----  
**SITework**

Driveway: 2" asphalt base coat of paving (finish coat not included) over 12" on-site gravel with 3" crushed gravel, 10'+/- wide. Length and/or turnaround will vary with plan  
Trees: Cut and removed as minimally required for construction.  
Stumps: Buried on site.  
Excavation: Excavation and removal of soils as required.  
Material: Importing of fill as required.  
Grading: Smooth final grade, using loam from site.  
Retaining walls: Site built retaining walls using boulders from site or landscaping blocks if required.  
Drainage: 4" perforated PVC perimeter drains inside and outside footings to 4" solid PVC gravity outfall "to daylight" (or sump basin and pump if topography requires).  
Sewer System: Town Sewer

**FOUNDATION AND BASEMENT**

Footings: 16"x8" concrete.  
Foundation: House: 8"x7'10" poured concrete.  
Garage: 8"x3'10" poured concrete. All foundation walls include steel anchor bolts.  
Columns: 3 1/2" concrete/steel lallys, as required.  
Piers: 24"x24"x8" concrete, under slab.  
Reinforcing: (3) Continuous rows #4 steel rebar in wall.  
Walls pinned to footing with rebar.  
Windows: Standard vinyl per plan.  
Window Wells: None.  
Water Proofing: (1) coat asphalt sealer applied on foundation wall below grade.  
Floor Slab: House: 4" thick (3000) psi concrete, over 8" depth stone bed. Garage: 4" thick (3000) psi concrete with steel reinforcing mesh, over compacted gravel.

**FRAMING**

Sills: (1) 2x6 pressure-treated, with sill seal and steel anchor bolts, plus (1) 2X6 KD plate.  
Joists: Per plan, per code, 16" on center (O.C.).  
Bridging: Solid wood blocking.  
Subflooring: 3/4" tongue and groove Advantech or equal; glued and nailed to joists.

Initial: Contractor: \_\_\_\_\_ Buyer: \_\_\_\_\_ Buyer: \_\_\_\_\_

Included by CBI: **White** duplex outlets and toggle switches per code, smoke /carbon monoxide detectors per code, (2) exterior outlets, (1) garage outlet, basement lights as required, (1) attic light, (2) exterior floods, 1 lamp/fan bathroom fixture per bathroom ; Master Bath to have the Energy Star Fan, (1) basement outlet, (1) basic doorbell with (1) button location, (15) Recessed Cans (White). Labor included to install pre-assembled standard light fixtures (interior and exterior) per plan. Walk-in closets to have ceiling lights, standard closets do not have lights.

Closet: Walk-in closets to have ceiling light. Standard closets do not have lights.  
Phone/Internet: Pre-wired for (3) jack locations using CAT 5E Cable; upgrades to CAT 6 and terminations available  
Cable: Pre-wired for (3) jack locations using RG 6. Owner to pay cable company for outlets/hook-up.

### **PLUMBING**

System: Baths, kitchen and laundry per plan.  
Fixtures: KOHLER or MOEN Fixtures provided and installed by CBI in Chrome finish. Upgrades available. Fiberglass Showers and/or Tubs per plan. Custom Tile Master Shower with Glass Door.  
Water: Tie into town water system.  
Hot Water: On-Demand Water Heater  
Laundry: Hook Ups Per Plan for washing machine; Slop sinks optional upgrade.  
Vented Ducts: 4" at baths, 4" at dryer, 4" passive radon from slab through roof.  
Sillcocks: (2) Frost-Proof.  
Gas Piping: To furnace and Fireplace.

### **HEATING**

System: Forced Hot Air with Central A/C  
Furnace: Gas fired, York or similar.  
Zones: 1-2 zones, to be determined by plan; first and second floor.  
Fuel Tank: Natural Gas.  
Radiation: Standard registers located at the discretion of the installer.  
Exhaust: Direct vent.

### **INSULATION**

Ceiling: R-49 fiberglass or R-30 in slopes, Upgrades available.  
Walls: "Flash and Batt" 2" spray foam polyurethane insulation w/3.5" R-13 fiberglass, R32 +/-  
Basement: R-30 fiberglass in ceiling.  
Garage Ceiling: R-30 fiberglass with conditioned space above only.

### **DRYWALL**

Material: 1/2" drywall all walls and ceilings first and second floors, smooth finish; fire code drywall in garage per code. Moisture resistant drywall as required.

### **INTERIOR PAINT**

Sherwin Williams or equivalent; Low VOC. (1) coat flat latex finish "Antique White" all walls over (1) coat latex drywall primer. Ceilings to be flat, primed w/ (1) finish coat flat white. (1) coat latex primer and (2) coat semi-gloss latex "Extra White" finish paint to be applied to all trim.

### **INTERIOR TRIM**

Doors: Choice of 2, 3, 4 or 6 panel solid molded doors with split jamb.  
Hardware: Schlage Lever Handles, Satin Nickel or Oil Rubbed Bronze finish.  
Door Trim: 1 x 4 Craftsman or 3 1/2" Colonial casing.  
Other Doors: Per plan.  
Baseboard: 5 1/4" Speed base.  
Window Trim: 1 x 4 Craftsman or 3 1/2" Colonial casing w/sills on first floor, picture framed 2<sup>nd</sup> floor.  
Closet: White coated wire closet organizers. Standard 12" single shelf/rod per closet, 4 shelves in pantry and linen closets.

Initial: Contractor: \_\_\_\_\_ Buyer: \_\_\_\_\_ Buyer: \_\_\_\_\_

**KITCHEN AND BATHROOM CABINETS, ETC.**

Yorktowne Maple Henning Cabinetry installed for kitchen and bathrooms as per original plan; choice of standard finishes. 48" Island and Group I or 2 Granite Countertops in Kitchen and bathrooms, cabinet hardware in choice of finishes.

**MIRRORS** By Owner.

**STAIRS**

Main Stairs: Hardwood Treads and Painted Risers from first to second floor, half wall with painted cap or railing per plan.

Other Stairs: Basement; plywood treads and risers.

**FINISH FLOORING**

Hardwood: Pre-finished 3 1/4" Red Oak or 3 1/4" Birch on Main First Floor.

Tile: Master Bath, Guest Bath, Laundry, Custom Tile Master Shower with Glass Door.

Carpet: Up Hall, Bedrooms and any additions and/or wings.

**APPLIANCES**

ENERGY STAR Rated Whirlpool appliances or equivalent; Gas stove, Microwave, and dishwasher in choice of White, Black or Stainless finish; Upgrades Available. CBI to install appliances supplied by CBI.

**LANDSCAPING**

Spread on-site loam, rake and seed disturbed areas. Landscaping per plan.

**WALKWAY:**

Concrete brick pavers from driveway to front door.

**MISCELLANEOUS**

Radon: Sub-slab piping vented through the roof. Further mitigation, testing, etc. by Buyer.

Cleaning: House and grounds to be left "broom" clean. Fine window cleaning to be done by Buyers.

Permits: Provided by CBI.

-----  
BUYER

BUYER

\_\_\_\_\_  
Date

\_\_\_\_\_  
Date

SELLER/CONTRACTOR

\_\_\_\_\_  
Jon L. Chinburg Date

Chinburg Builders, Inc.

Initial: Contractor: \_\_\_\_\_ Buyer: \_\_\_\_\_ Buyer: \_\_\_\_\_

Underlayment: 3/8" Plywood

Wall Height: Per plan.

Exterior walls: 2x6 studs, 16" O.C.

Interior walls: 2x4 studs, 16" O.C.

Beams: Built-up 2x's or LVL's, as required.

Headers: Solid built-up 2x's and plywood as required.

Ceiling Joists: 2x's per plan, per code, 16" O.C.

Strapping: 1x3, 16" O.C.

Wall Sheathing: Zip System, 1 1/2", 6 R-Value Sheathing

Siding: Certainteed brand "Mainstreet" vinyl siding or equivalent in choice of standard colors.

Trim: Vinyl and metal wrapped trim or similar, as required per plan.

Rake overhang: Per plan.

Roof Rafters: Per plan, per code, 16" O.C.

Roof Sheathing: Zip roof system.

Roofing: Asphalt, architectural **Black** shingles.

Snow Belt: 36" row of bituminous ice and water shield at bottom edge of roof.

Flashing: Aluminum or lead as necessary.

Ventilation: Continuous ridge vents and continuous soffit vent.

#### **FRONT STEPS**

Per Grade. Up to two Granite Steps or composite steps and decking, using pressure treated joists, on 12" concrete piers set 4' below grade. Vinyl Railings if required per code.

#### **REAR DECK OR PATIO**

Patio or Composite decking with White Vinyl Rails and wrapped rim boards and stringers.

**FIREPLACE** Direct Vent Gas Fireplace per plan

**WINDOWS** *Paradigm* or similar, white all vinyl windows with Low E insulated glass, screens and white grills between panes, per plan.

**SHUTTERS** Optional Upgrade.

#### **EXTERIOR DOORS**

Front Door: 3-0x6-8 insulated door per plan

Garage to house: Insulated, fire rated per code.

Slider Door: Vinyl Sliding patio door with screen per plan.

Side Doors: Insulated door per plan

Thresholds: Aluminum.

Hardware: Schlage locksets in choice of Satin Nickel or Oil Rubbed Bronze finish, keyed alike. (Patio doors normally require hardware supplied by manufacturer).

Casing: 1x4" flat casing.

Garage Doors: Carriage Style insulated garage door with Openers and Keypad and top panel Windows.

#### **EXTERIOR PAINT**

2 finish coats applied to exterior doors. Garage doors are installed with a factory finish.

**NOTE:** *Specifications from this point forward apply to heated living space only. Unheated, unfinished space to be completed at the minimum acceptable to meet code.*

#### **ELECTRICAL**

Service Size: 200 amp underground service. Meter located on house as determined by utility guidelines and CBI discretion.

Fixtures: Electrical fixtures per plan supplied by CBI, Upgrades available.

Initial: Contractor: \_\_\_\_\_ Buyer: \_\_\_\_\_ Buyer: \_\_\_\_\_